



Sewer Tap Application

**WWTP Needs at least
24 hours notice
to make tap!**

City of McCook
505 West C Street * PO Box 1059
McCook, NE 69001
(308) 345-2022 * Fax (308) 345-1461
www.cityofmccook.com

Repair Existing Service
New Service

Please provide sketch of existing & proposed conditions.

Job Address: _____

Property Owner

Name: _____

Address: _____

City/State/Zip: _____

Phone: _____

Owner installation: This installation is being made on property that I own, which is not intended for sale, lease, rent, or exchange.

Owner signature: _____

Date: _____

Contractor

Business name: _____

Address: _____

City/State/Zip: _____

Phone: _____

Authorized signature: _____

Date: _____

Is Contractor licensed? Yes No



Distance from House to Main _____

Depth of Sewer Line _____

Location of Sewer Main _____
(Street, Alley, Other)

Office Use Only

Type and Size of Sewer Line

Type _____

Size _____

Type and Size of Sewer Main

Type _____

Size _____

Sewer Tap Made By

Name _____

Date and Time _____

City Staff Name: _____

Date: _____

§51.021 PLUMBER LIABILITY.

The licensed plumber who connects with the public sewers shall be held responsible on his or her bond for any damages he or she may cause to the sewers, public streets, or alleys. He or she shall restore the streets or alleys to the satisfaction of the Sewer Inspector, and make good any settlement of ground or pavement caused by the excavations made by him or her under, or by virtue of, any permit issued under the provisions of this chapter. In the event of ground settling within one year after being refilled, the Sewer Inspector shall have the right and it shall be his or her duty to demand and require the restoration of the same by the party who made the excavation.

§51.004 EXCAVATIONS.

(D) Trenches greater than five feet in depth shall be properly braced and shored, and the party excavating shall be liable for all damages arising by reason of any neglect in this respect.

(E) Trenches shall be sheeted, shored and braced as necessary to comply with all applicable laws, codes, ordinances, rules, and regulations. Compliance with this requirement shall rest solely with the contractor. The sheeting, shoring and bracing shall not be removed until backfilling has progressed to a stage that no damage to utilities or structures will result from its removal.

(F) Brace trenches running near walls or columns to prevent any settlement or other disturbance of walls or columns. Make trench excavation that runs parallel to footing bottom with maximum slope of one to one.

(G) The contractor shall contain his or her work to public street and highway rights-of-way and easements or shall be liable to damage claims for any damages resulting from his or her operation.